



The back of house or BOH encompasses all the areas that are not accessible to customers.

Back of House Lighting



TABLE OF CONTENTS

O1 SPOT LIGHT



O2 DOWN LIGHT



O3 PANEL LIGHT



O4 CEILING



O5
MIRROR
LIGHT



07WEATHERPROOF LIGHT

O8
HIGHBAY



The back of house or BOH encompasses all the areas that are not accessible to customers. These include commercial, residential and hospitality areas from service entry to service exit. The back of house projects require an optimal balance of comfortable aesthetics and energy efficiency, technological upgrades and cost effectiveness.





7\\\





595lm 850lm



2700K 4000K 5000K

DESCRIPTION

Adopts CREE LED technology with lens to control glare and beam,

Special designed die cast aluminum heatsink to resist the heat

Made with powder coated die cast aluminum with stainless steel spring for easy installation

Best replacement for traditional halogen Function: On/Off, O-10V, Triac, Dali, Emergency



24° 36° 60°



Ø60 Ø70 Ø83



IP44 IP65

www.wilmarintl.com

SERIES SERIES

04

O1 SPOT LIGHT









1120lm 2250lm 2850lm 4000lm 4200lm 4700lm

2700K 4000K 5000K

24° Ø90 36° Ø125 60° Ø150 Ø200

IP54







Matt silver reflector



White reflector



Bright silver reflector

Adopts CITIZEN COB high efficiency with 114lm/W

Body and trim made with die cast aluminum with powder coated

Traditional deep bright silver reflector (UGR<19) brings a good lighting effect for human beings.

Function: On/Off, 0-10V, Triac, Dali, Emergency

Easy to install, use stainless steel spring, safe and durable











10W 18W 25W 35W 42W



960lm 1980lm 2750lm 3570lm 4750lm



2700K 4000K 5000K



90°



Ø90 Ø120 Ø160 Ø200



IP54



DESCRIPTION

Boosts its ultra slim design and flat cover

Adopts high lumen SMD LED & PC diffuser to ensure the soft and uniform light.

06


ADC12 aluminum profile privdes excellent heat dissipation.

Offering 90° beam angle in different wattage

Function: On/Off, 0-10V, Triac, Dali, Emergency

Easy to install, use stainless steel spring, safe and durable





VAIBS series premium quality led panel light adopts high grade of EPISTAR LED light source with 100lm/W lumen output UGR<19 can meet the most strict design and energy saving

No UV & IR emission.

Extruded aluminum frame is high grade powder coating for long life

Life span up to 50000Hrs

Function: On/Off, O-10V, Triac, Dali, Emergency







3200lm



2700K 4000K 5000K



110°



IP20 IP65



600x600 1200x300







Adopts high lumen SMD LED & PC diffuser with even light output.

Up to 70% energy saving compared to

standard CFL

Offering 90° beam angle in different wattage

Function: On/Off, O-10V, Triac, Dali, Emergency

Easy to install, use stainless steel spring, safe and durable



12W 18W 25W 30W



1260lm 1910lm 2575lm 3090lm



2700K 4000K 5000K



120°



IP54



Ø250 Ø300 Ø350 Ø400

O4 CEILING LIGHT



















780lm 1170lm 1560lm



3000K 4000K 6500K



Diffused



IP44



420x60x40 665x60x40 965x60x40



Stainless Steel



Matt Black

Adopts SMD2835 LED as a light source Luminaire made with stainless steel, aluminum and acrylic

It has two

09

Function: On/Off, O-10V, Triac, Dali, Emergency

Easy to install, with mounting clip





06
BULKHEAD
LIGHT



15W 20W 10W



1200lm 1700lm 800lm



2700K 4000K 5000K



120°



IP65



Ø275 220x135



DESCRIPTION

Die cast aluminum lamp body, excellent heat dissipation

Milky white PC cover, high impact resistance IK10 approval

Stainless steel hexagon socket end cap screw

Function: On/Off, O-10V, Triac, Dali, Emergency, motion sensor, dimming sensor, RF sensor

Energy saving, not emitting UV and IR, no RF interference



IP65 waterproof Led light , PC housing resistant to UV & impacts, Silicon gasket Quality SMD 2835 LED chips, life time more than 50000 Hours Inbuilt brand LED driver , Opal PC cover with light diffusing agent, light transmittance up to 85% Function: On/Off, Emergency, motion sensor, dimming sensor, RF sensor



20W 40W 60W



2000lm 4000lm 6000lm



2700K 4000K 5000K



120°



IP65



550x70 1200x70 1450x70



BRAVE SERIES

O7WEATHERPROOF
LIGHT

IP65 waterproof Led light, PC housing resistant to UV & impacts, Silicon gasket Quality SMD 2835 LED chips, life time more than 50000 Hours Inbuilt brand LED driver,

Opal PC cover with light diffusing agent, light transmittance up to 85% Function: On/Off, Emergency, motion sensor, dimming sensor, RF sensor



18W 38W 57W



2160lm 4560lm 6840lm



4000K 5000K



120°



IP65



1150x76 1450x76

WEATHERPROOF LIGHT











100W 150W 200W 240W



13000lm 19500lm 26000lm 31200lm



2700K 4000K 5000K



110°



IP65



Ø250 Ø330



DESCRIPTION

Adopts SANAN LED as a light source with high lumen of 130lm/W Body & heat sink made with die cast aluminum with PC diffuser and Cover

Thermal convection design speed up the heat dissipation through temperature difference convection

Radiator-fan heightened effectively increase the radiant area





10W 18W 25W 35W 42W



960lm 1980lm 2750lm 3570lm 4750lm



2700K 4000K 5000K



90°



Ø90 Ø120 Ø160 Ø200



IP54



DESCRIPTION

Adopts EPISTAR LED as a light source with high lumen of 170lm/W Body & heat sink made with die cast aluminum powder coated finish with Polycarbonate lens

Outsstanding performance on heat management is attributable to the omnidirectional nature of tree-like finsallowing air streams to enter and exit from all direction Function: On/Off, Dali, 1-10V, Occupancy control
































WILMAR INTERNATIONAL LLC

Headquarter

F108 West 13th Street Wilmington

New Castle, USA | Dubai, UAE

T: +971 4 5149633 | F: +971 4 5144337

www.wilmarintl.com | info@wilmarintl.com

Regional Office: Middle East

Wilmar International LLC









