

CEILING RECESSED

Art Number WI 111011

Model

IP44





Ø80

Features

Die cast aluminum body with high quality of powder coating

Special designed die cast aluminum hear sink to dissipate the heat

Good quality COB led technology with lens to help to protect from the glare

and accurate the beam angle

Stainless steel spring for easy ceiling installation

Available fixed and tilt able model with 7W and 10W

IP65 grade fixed model can use in various application where need the high

protection from water, dust and steam. Dimming with Triac, Dali and 0-10V

Product Specification

LED Chip CREE LED 7W Power

Input 100-240VAC Remote Driver

Output 595lm

CCT 2700K(27)/3000K(30)/4000K(40)/6000K(60)

LED Qty COB LED

Technical Data

IP Rating IP44

Housing/Front Cover Die cast aluminum

Finishing White with sand(02)/Black with sand(04)

Diffuser Lens

Power Cable $HO5RN-F 2x0.75 \text{ mm}^2/ L=0.5 \text{m} \text{ (low voltage)}$

Mounting Sleeve Stainless steel spring


Cutout Ø60mm Tilt/Rotate 40° Weight 0.3 Kg Package 30pcs/CTN

Photometric Light Distribution




7W 3000K 36°

UNIT:cd - C0/180,28.2deg - C90/270,28.0deg



7W 3000K 60°



Photometric Data

80

Luminous Eficacy 85lm/W

24°(24)/36°(36)/60°(60) Beam Angle

Operating Temp. -20°C~+50°

Order Code Example

Artnumber WL111011

Finish PAW(02)

Beam Angle 50°(50)

Color Temp 3000K(30)

WL111011.02.50.30