


CEILING RECESSED 13W

Art Number


Model







Photometric Light Distribution



Optional Combination



Type 1-1



Type 2-1



Type 3-1



Type 3-2



Type 4-1



Type 4-2



Type 5-1

Accessories







Honeycomb Louver Diffusion Sheet

Features

LUKAS Series adopts High lumen efficiency CITIZEN led as a light source

It designed with removable light engine, which can be assembled or disassembled by twisting the light engine

Body & bezel made with aluminum die cast and plastic-PC reflector gives good

Forged aluminum heat sink resist the heat dissipation.

Available optional combination used the round trim less trim, which can be joined together and becoming multiple lights by connecting recessed trim less and recessed trim less plank.

Each single kit can be connected into trim less configurations.

The lights can be easily arranged into a rectangles made of two.

Lifespan is up to 50,000 hrs.

Easy to install, use stainless steel blade, safe and durable

Available other CCT on Request

Product Specification

LED Chip CITIZEN LED

Power 13W

Input 90-264 VAV with Remote Driver

Lumen 1329lm

CCT 3000K(30)/4000K(40)/5000K(50)

LED Type COB LED
Power Factor PF>0.9

Technical Data

IP Rating IP44

Housing/ Front Cover Die cast aluminum
Finishing White(02)/ Black(04)

Reflector Plastic-PC

Power Cable $\frac{\text{HO5RN-F 3x0.75 mm}^2}{\text{L=0.5m}}$

Mounting Sleeve Stainless steel
Cutout Ø68mm
Class II

Photometric Data

Luminous Eficacy

CRI 90

Beam Angle 15°(15)/ 24°(24)/ 38°(38)/ 60°(60)

102lm/W

Operating Temp. -20°C~+45°

Order Code Example

Artnumber WL111043 Finish WH(02)

Beam Angle 60°(60)

Color Temp 3000K(30)

WL11104302.60.30

