


Art Number
WL221016

Model
4.5W 220-240VAC



Features

- ELLIE Series surface mounted downlight adopts quality CREE led as a light source
- Body made with aluminum die cast in closed chamber for dust free
- Versatile design surface mounted and available with recessed trim or trim less and pendant light
- Each design have different size and wattage available
- Small aperture conveys a distinctive architectural or high-tech appearance
- Baffle available in white, black, champagne and silver up on request



Product Specification

LED Chip	CREE LED
Power	4.5W
Input	220-240VAC
Output	349lm(2700K)/ 410lm(4000K)/ 481lm(5000K)
CCT	2700K(27)/ 4000K(40)/ 5000K(50)
LED Qty	1 COB LED
Driver	Philips/ Tridonic

Technical Data

IP Rating	IP20
Housing	Die cast aluminum
Front Cover	Clear tempered glass
Finishing	White with sand(02)/ Black with sand(04) grey with sand(07)
Power Factor	PF>0.9

Photometric Data

CRI	90
Luminous Efficacy	77lm/W
Beam Angle	20°(20)/ 40°(40)
Operating Temp.	-20°C-+35°

Order Code Example

Artnumber	Finish	Beam Angle	Color Temp
WL221022	PAW(02)	60°(60)	2700K(27)
WL221022.02.60.27			