

Flood light 100W IP66

Art Number WI 771017

100W 220-240VAC





Features

Available variety of mounting accessorie along with the luminaries such as wall mounted, ceiling mounted, pole mounted and ground mounted

Wide range of lumen output from 130lm to 140lm

User friendly driver compartment with built in

Available in different dimming options such as DALI/ 1-10V

Available in 100W/150W/200W/250W/300W

Product Specification

LED Chip LUMI LED 100W Power

Input 220-240 VAC, 50/60Hz


Output 13000lm(A18)/13500lm(60°)/14000lm(110°) CCT 3000K(30)/4000K(40)/5000K(50)/6000K(60)

Power Factor >0.95 Driver **Philips**









469

Technical Data

IP Rating IP66 IK Rate IK08

Housing Die cast aluminum Heat sink Die cast aluminum Finishing Anodised grey (06)

Lens Polycarbonate tempered glass

HO5RN-F 3x0.75 mm²/ L=0.5m (high voltage) Power Cable

Mounting **SPCC**

Photometric Data

Luminous Eficacy 130lm-140lm/W

60°(60)/110°(110)/80°x130°(A18) Beam Angle

Operating Temp. -30°C~+50°

Accessories







Wireguard







Order Code Example

Artnumber

Finish AGŞ(06) Beam Angle 60°(60)

Color Temp 3000K(30)

WL771017.06.60.30