

Flood light 250W IP66



Model 250W 220-240VAC

IP66 **ा** ।K08 0 00001



611

399

(60°)

Light Distribution Curve

Features

Available variety of mounting accessorie along with the luminaries such as wall mounted, ceiling mounted, pole mounted and ground mounted Wide range of lumen output from 130lm to 140lm User friendly driver compartment with built in Available in different dimming options such as DALI/ 1-10V Available in 100W/150W/200W/250W/300W

Product Specification

Те

Mounting

CRI

Photometric Data

Luminous Eficacy

Operating Temp.

Beam Angle

LED Chip	PHILIPS LED		
Power	250W		
Input	220-240 VAC, 50/60Hz		
Output	32500lm (A19) / 32500lm (A18) / 33750lm (60°) /		
	35000lm (110)		
CCT	3000K (30) / 4000K (40) / 5000K (50) /6000K (60)		
Power Factor	>0.95		
Driver	Philips		
Technical Data			
IP Rating	IP66		
IP Rating IK Rate	IP66 IK08		
0			
IK Rate	IKO8		
IK Rate Housing	IK08 Die cast aluminum		
IK Rate Housing Heat sink	IK08 Die cast aluminum Die cast aluminum		
IK Rate Housing Heat sink Finishing	IK08 Die cast aluminum Die cast aluminum Anodised grey (06)		

A19(40°x80°)

A18(80°x130°)



Accessories







Wireguard



(110°)



70

130lm-140lm/W

-30°C~+50°

60°(60)/110°(110)/80°x130°(A18)/40°x80°(A19)

SPCC

Order Code	Example			
Artnumber WL771020	Finish AGS(06)	Beam Angle 60°(60)	Color Temp 3000K(30)	
WL771020.06.60.30				



www.wilmarintl.com