


**Art Number** WL891021  
**Model** 3W



## Features

LAYIKKA series LED wall step light designed wide beam with unique and simple structure.

Body made with extruded/ die cast aluminum with clear tempered glass diffuser. It adopts CREE led as a light source.

As a standard a recessed box is also included for concrete applications.

IP65 fixture is suitable in indoor, outdoor and architectural lighting application.

## Product Specification


|                        |   |
|------------------------|---|
| LED Chip               | CREE LED                                  |
| Power                  | 3W  |
| Input                  | 100-240VAC integrated Driver              |
| Lumen                  | 200lm                                     |
| CCT                    | 2700K(27)/3000K(30)/ 4000K(40)/ 5000K(50) |
| High Color Consistency | <3 SDCM                                   |
| Class                  | Class II                                  |

## Technical Data

|              |   |
|--------------|---|
| Power Factor | >0.9                                    |
| IP Rating    | IP65                                    |
| IK Rating    | IK06                                    |
| Housing      | Extruded aluminum profile               |
| Diffuser     | Clear tempered glass                    |
| Finishing    | White(02)/ Black(04)/ Grey(06)          |
| Power Cable  | H05RN-F 3x0.75 mm <sup>2</sup> / L=0.5m |
| Installation | Wall recessed                           |

## Photometric Data

|                   |                           |
|-------------------|---------------------------|
| CRI               | 80                        |
| Luminous Efficacy | 66lm/W                    |
| Beam Angle        | 50°(50) <i>Asymmetric</i> |
| Operating Temp.   | -20°C-+50°                |



## Order Code Example

| Artnumber         | Finish | Beam Angle     | Color Temp |
|-------------------|--------|----------------|------------|
| WL891026          | WH(02) | Asymmetric°(A) | 3000K(30)  |
| WL891026.02.36.30 |        |                |            |