


Art Number	Model
WL891029	10W



Features

- Die cast aluminum lamp body, excellent heat dissipation
- IP65 waterproof, dustproof for indoor and outdoor lighting
- Milky white PC cover, high impact resistance IK10 approval
- Stainless steel hexagon socket end cap screw
- Can be installed with a motion sensor, dimming sensor, RF sensor
- Available for emergency function 1-3Hrs
- Energy saving, not emitting UV and IR, no RF interference

Product Specification

LED Chip	EPISATAR SMD LED
Power	10W
Input	85-265VAC integrated Driver
Output	800lm
CCT	2700K(27)/ 3000K(30)/ 4000K(40)/ 6000K(60)
LED Type	SMDLED

Technical Data

Power Factor	>0.9
IP Rating	IP65
IK Rate	IK10
Housing/ Front Cover	Die cast aluminum alloy
Finishing	White(02)/ Black(04)/ Grey(06)
Diffuser	PC

Photometric Data

CRI	80
Luminous Efficacy	80lm/W
Beam Angle	120°(120)
Operating Temp.	-40°C-+60°

Order Code Example

Artnumber	Finish	Beam Angle	Color Temp
WL891029	WH(02)	120°(120)	3000K(30)
WL891029.02.120.30			