

Art Number WI 891033

Model 3W

Wall light <u>3W IP67</u>







Ø33

80



structural optical design, concentrated and soft light output. Body constructed with CNC aluminum and sleeve made with stainless steel. There are different type of front cover

Dimmable support: Triac, PWM, 1-10V, Dali, DMX 512


Fronted or diffused glass

Product Specification

LED Chip	CREE LED
Power	3W
Input	100-240VAC with integrated Driver
Lumen	210lm
CCT	2700K (27) / 3000K (30) / 4000K (40) / 6000K (60)
	Red (05) / Green (06) / Blue(07)
LED Type	High Power Led

Mounitng sleeve





H[m]	D[m]	MaxLux	MedLux	
0.40	1.04	242	73	
0.80	2.07	60	18	
1.20	3.11	27	8	
1.60	4.15	15	5	
2.00	5.19	10	3	


Technical Data

IP Rating	IP67
IK Rating	IK07
Housing/ Front Cover	Anodized aluminum
Finishing	White (02)/ Black (04) / Grey (06)
Diffuser	Frosted Glass
Mounting Sleeve	Stainless steel
Power Cable	H05RN-F 3x0.75 mm²/ L=0.5m 100-240VAC

Photometric Data

CRI	80
Luminous Eficacy	70lm/W
Beam Angle	120° (120
Operating Temp.	-30°C~+

V 0) +50°





We reserve the right to make technical changes without prior notice Electrical/Optical data are subjected to a tolerance of +/-10%

www.wilmarintl.com