



Art Number	Model
WL891042	40W 100-240VAC



Features

- Die cast aluminum lamp body, excellent heat dissipation
- IP65 waterproof, dustproof for indoor and outdoor lighting
- Milky white PC cover, high impact resistance IK10 approval
- Stainless steel hexagon socket end cap screw
- Can be installed with a motion sensor, dimming sensor, RF sensor
- Available for emergency function 1-3Hrs
- Energy saving, not emitting UV and IR, no RF interference



Product Specification

LED Chip	EPISATAR LED
Power	40W
Input	85-265VAC integrated Driver
Output	3600lm
CCT	3000K(30)/ 4000K(40)/ 6000K(60)
LED Type	SMDLED

Technical Data

IP Rating	IP65
IK Rate	IK10
Housing/ Front Cover	Die cast aluminum alloy
Finishing	White(02)/ Black(04)/ Grey(06)
Diffuser	PC
Mounting	Wall Mounted, Ceiling Mounted

Photometric Data

CRI	80
Luminous Efficacy	90lm/W
Beam Angle	120°(120)
Operating Temp.	-40°C-+60°

Order Code Example

Artnumber	Finish	Beam Angle	Color Temp
WL891040	WH(02)	120°(120)	3000K(30)
WL891040.02.120.30			